

P-LOCK POWER CORDS

C14 to C13

P-Lock

Secure the PDU-side connection in high-density installations and help prevent accidental power disconnection.



PDU-SIDE POSITIVE LOCKING

P-LOCK C14 PLUG
power-source end

C13 CONNECTOR
equipment end

CONNECTION	RATING	LOCKING END	TEMPERATURE
C14 to C13	10 A / 250 V	PDU side	-20 C to +70 C

Locks at the PDU end

The C14 P-Lock plug provides patented retention in a compatible locking PDU outlet. The standard C13 equipment end remains non-locking.

POWER SOURCE

C14 P-Lock plug

EQUIPMENT

C13 connector

Check outlet compatibility

P-Lock mates electrically with standard C13 outlets. Positive locking engages only in a compatible locking outlet.

APPLICATIONS

Data centres | Server rooms | High-density racks

VDE / RoHS by selected SKU

Stocked P-Lock range

No MOQ | Live availability online

H05VV-F 3G0.75

LENGTH	○ BLACK	● BLUE	● RED
0.5 m	MK6110	MK6120	MK6130
1.0 m	MK6210	MK6220	MK6230
1.5 m	MK6410	MK6420	MK6430

H05VV-F 3G1.0

LENGTH	○ BLACK	● BLUE	● RED
2.0 m	MK6610	MK6620	MK6630
2.5 m	MK6710	MK6720	MK6730
3.0 m	MK6810	MK6820	MK6830

More lengths and configurations

Other lengths, colours and configurations are available on request, subject to MOQ and lead time.


[VIEW CURRENT STOCK](#)