

RACK POWER, CLEARLY SPECIFIED

Power cords for data centres

Standard, locking and specialist IEC 60320 cords for racks, PDUs, UPS systems and critical

EU SUPPLY FROM CZECH STOCK

Custom configurations quoted for project requirements



CONNECTIONS

C14-C13 · C14-C15 · C20-C19

LOCKING

P-Lock · WS-Lock · D-Lock

OPTIONS

Colours · lengths · LSZH

SUPPLY

Czech stock · custom

Choose the connection

[CLICK A FAMILY TO VIEW THE RANGE](#)

STANDARD RACK LINK

C14 to C13

Everyday PDU or UPS connection to equipment with a C14 inlet.

10 A / 250 V · 3G0.75 or 3G1.0



HOT-CONDITION INLET

C14 to C15

For equipment fitted with a C16 hot-condition inlet.

10 A / 250 V · H05V2V2-F 3G1.0



HIGHER CURRENT

C20 to C19

For suitable higher-current PDUs, UPS systems and equipment.

16 A / 250 V · H05VV-F 3G1.5



Lock the end that matters



P-Lock

PDU-SIDE RETENTION



Locks into a compatible locking C13 PDU outlet; the equipment end remains standard.



WS-Lock

EQUIPMENT-SIDE RETENTION



Secures to a standard C14 equipment inlet; no proprietary device inlet is required.

BOTH ENDS

Choose D-Lock where a compatible locking PDU outlet is available.

Specify the cable, identification and supply route

COLOUR + LENGTH

Common 0.5-3.0 m · varies by family



CABLE OPTIONS

PVC · LSZH · thicker conductors

Select by connection, load and installation.

STOCK + CUSTOM

Czech-held stock for standard needs

Custom builds confirmed and quoted individually.

[SEND US SIX DETAILS](#)

Connector pair · rating · cable · length · colour · quantity

We will match a stocked item or quote the right custom production route.

CONTACT MK CABLE



Confirm connector compatibility, current rating and product-specific approvals before ordering.